

Product Data Sheet: DRG Series Decorative Wall Mounted Door Retainers



Description

Electromagnet Fire Door Holders are designed to hold open Fire Doors in any areas where easy access is essential, and can be used in conjunction with any fire alarm system. When an alarm is triggered, power to the door holder is cut allowing the fire door, with its standard closing mechanism, to shut automatically.

The decorative door retainers look superb and are available in Bright Chrome, Lacquered Brass or Stainless Steel finishes and are particularly suitable for use in prestigious installations - Offices, Hotels, Conference Centres etc.

The keeper plate for the DRG door holder is supplied with a matching surface finish and a push button manual release switch. The magnet is supplied with a standard single gang electrical back box, which enables the unit to be flush mounted. If required, a surface mounting kit is available in matching finishes, with two 20mm entry holes and blanking plugs.

Technical Information

Part No.	DRG-*	DRG-*-230V
Supply Voltage:	24Vdc \pm 10%	230V ac \pm 10%
Holding Force @ 24V:	200N	
Residual Holding Force:	0	
Current Consumption:	15mA	144mA
Ambient Temperature:	0 - 40°C	
Door Closing Power:	3 - 6	
Current Consumption:	66mA	
Weight (per unit packed):	500g	
*denotes surface finish: CH Bright Chrome, BR Lacquered Brass and SS Stainless Steel.		

Dimensions

