



ReSet Manual Call Points (Single and Double Pole)

The Cranford Controls' ReSet Manual Call Points are designed to mimic the feel of breaking glass, whilst offering the user the benefits and environmental advantages of a re-settable operating element. The ReSet Manual Call Points are available with either single or double pole changeover contacts that can be wired to suit a variety of applications and are safe to use in areas such as food processing plants and leisure centres where glass cannot be used such

As the units can be simply reset, they provide an ideal solution for areas that suffer from a high number of false activations such as schools, shopping centres along with a variety of other public places. The waterproof versions are specially designed for use within harsh environments such as oil rigs, ships, factories, as well as wash down areas that are sensitive to broken glass.

The dual mount variants are provided with a surface mount back box and flush mount wall plate as standard.



Features

- Single or double pole changeover versions available
- Waterproof models available - tested to IP67
- Extremely attractive, high value look and feel: glass appearance maintains operator deterrence, whilst a visible warning flag confirms activation.
- Low profile, heavy-duty terminations.
- Easy installation - no glass elements that could be broken or incorrectly fitted.
- Optional integral cover can be fitted to prevent accidental activation.
- Complete functional test with every activation.

Specifications

Surface mounted	20mm knock out conduit entry points		
Operating Temp	-20°C (-4°F) to 65°C (149°F).		
Dimensions:	Height (mm)	Width (mm)	Depth (mm)
Flush (indoor)	87	87	23
Surface (indoor)	87	87	58
Waterproof	90	89	71

Method of Operation

**Step 1:**

Positive action - mimics the feel of breaking glass.

**Step 2:**

A warning indicator drops into view when the call point is activated.

**Step 3:**


To reset a simple key is inserted into the bottom of the call point.

**Step 4:**

A quick turn of the key and the call point is reset and ready for use again straight away.


Connection Details

SPCO-Series 2



Denotes a ReSet call point that is fitted with a single pole changeover switch both the normally open and normally closed contacts are easily accessed through the installer terminals as illustrated.

Series 11



Denotes a ReSet call point that incorporates two independent single pole changeover switches providing double pole changeover contacts. Easily accessed through the installer terminals as illustrated.

Part Numbers

308-115	Red SPCO Flush and Surface Mount
308-227	Blue SPCO Flush and Surface Mount
308-225	Orange SPCO Flush and Surface Mount
308-104	Green SPCO Flush and Surface Mount
308-142	Yellow SPCO Flush and Surface Mount with 'Gas Release' text
308-226	White SPCO Flush and Surface Mount with 'Panic Alarm' text
308-154	Re-set integral polycarbonate cover - no text
308-143	Green DPCO Flush & Surface with 'Running Man' logo

Additional product variants are available. For further information, please contact the Cranford Controls' Customer Service Team.

Accessories